



SPECIALTY CASES

[DESIGN ■ SUPPORT ■ PROTECT]

Product Datasheet

SKB 3SKB Series

3SKB-R908U30

Specifications

Lid Depth	4.50 in	11.43 cm
Interior Length	TBA	TBA
Interior Width	19.00 in	48.26 cm
Interior Height	14.00 in	35.56 cm
Interior Cu. Volume	4.62 cu ft	0.13 cu m
Space Units Total	8	8
Rackable Depth	30.00 in	76.20 cm
Depth Front Rail to Back Lid	34.50 in	87.63 cm
Exterior Depth	TBA	TBA
Exterior Width	TBA	TBA

Exterior Height	TBA	TBA
Exterior Cu. Volume	15.12 cu ft	0.43 cu m
Carton Length	43.50 in	110.49 cm
Carton Width	26.50 in	67.31 cm
Carton Depth	23.50 in	59.69 cm
Carton Cu. Volume	15.68 cu ft	0.44 cu m
Product Weight	76.80 lb	34.84 kg
Shipping Weight	88.00 lb	39.92 kg
Color	Black	Black

Description

SKB's 30" deep rotomolded shock rack which should be an instant success with all companies utilizing the deeper servers such as the new Dell and Compaq. Nobody else manufactures a rotationally molded shock rack that is 30" deep and that fits inside the center portion of the case.

Standard features include: (patent pending) compound hinged doors, black powder coated stainless steel latches, removable 4" casters. The inner rack chassis is built of high strength / lightweight aluminum alloy and 11-gauge hot rolled carbon steel rack rails to DIA-310 standards. Shock and vibration mitigation is accomplished with eight (8) elastomeric isolators rated for a payload range of 40 lbs. to 150 lbs. in a standard configuration and up to 300 pounds in a special order extended payload configuration allowing adequate sway space for ambient air circulation and heat dissipation with gasketed doors and pressure relief valve. The rack rails come pre-threaded for standard 10-23 hardware and mounting screws are included.

Features

- 8U rack rails front and rear
- Patent pending compound hinged doors
- Threaded steel rails
- Rear rails
- Casters
- Shock and water resistant
- Gasketed doors
- Pressure relief valve
- Stainless steel key-lockable field replaceable latches
- Removable 4" casters standard
- Stacks securely with the wheels on or off
- Recessed latches
- Adjustable elastomer shock absorbers
- Provisions to add additional shocks
- Roto molded for strength

P.O. Box 936
Sykesville, MD 21784
www.SpecialtyCases.com

Phone: 301-497-9032
Toll Free: 800-267-1674

Last Updated
January 2023