



SPECIALTY CASES

[DESIGN ■ SUPPORT ■ PROTECT]

Product Datasheet

SKB 3SKB Rolling Series

3SKB-R08U20W

Specifications

Lid Depth	3.25 in	8.26 cm
Interior Length	TBA	TBA
Interior Width	19.00 in	48.26 cm
Interior Height	14.00 in	35.56 cm
Interior Cu. Volume	3.08 cu ft	0.09 cu m
Space Units Total	8	8
Rackable Depth	20.00 in	50.80 cm
Depth Front Rail to Back Lid	22.75 in	57.79 cm
Exterior Depth	23.25 in	59.05 cm
Exterior Width	28.5 in	72.39 cm

Exterior Length	31 in	78.74 cm
Exterior Cu. Volume	11.37 cu ft	0.32 cu m
Carton Length	TBA	TBA
Carton Width	TBA	TBA
Carton Depth	TBA	TBA
Carton Cu. Volume	TBA	TBA
Product Weight	56.00 lb	25.40 kg
Shipping Weight	64.00 lb	29.03 kg
Color	Black	Black

Description

The Rolling Shockmount Case series incorporates our black powder coated twist latches with locking loops and low profile injection molded pull handle with a 20 inch deep tough shell. The molded design provides extra stiffness in the lids and sides and allows for secure stacking. Rack depth front to rear rail is 20 inches and each lid is 2-1/4 inches deep. Rack rails are pre-threaded for standard 10-32 hardware and the mounting screws are included. Doors are fully usable even when racks are stacked together. Elastomeric shocks protect even the heaviest of loads. Sliding retractable handle, ambient pressure relief valve, oversized snap-down handles on each side, roller blade wheels, and gasket protected front and rear doors are all standard equipment.

Features

- Black powder coated twist latches with locking loops
- Threaded steel rails
- Rear rails
- Built-in wheels
- Shock and water resistant
- Low profile pull handle
- Mounting hardware is included