# 3RR SERIES

## 30" REMOVABLE SHOCK RACKS

*When maximum shock absorption is needed with a sliding rack in the smallest exterior dimensions, this is the choice for this depth*



*Removable shock rack with patented "positive lock" latching system that slides open like a drawer*

## FEATURES

- Completely removable frame for access to bench integration
- Meets or exceeds MIL-STD-810G/IP67
- Standard payload range 40 to 150 lbs
- Optional extended payload range 160 to 300 lbs (3SKB-SA*)
- Standard 19" rack width per ANSI/EIA-310-C
- Standard rack depth 30" rail to rail
- Square hole rack rails to accommodate either #10-32 US standard, or 6mm international standard cage nuts - hardware included
- 2" front lid, and 5" rear lid with edge casters (standard); other options available
- SKB's rugged roto-molded shell ensures industry leading strength and impact resistance
- Molded in stacking ribs and lugs are designed to stack with competitive manufacturers' cases
- Black powder coated stainless steel hardware (standard) which is recessed for protection
- 8 comfort grip spring loaded lift handles
- Automatic ambient pressure relief valve (standard)
- Lid hangers (standard)
- Case coupling straps (standard)

## AVAILABLE SIZES

| Model # | Lid Depth Front | Lid Depth Rear | Rack Units | Rack Height |
|---|---|---|---|---|
| 3RR-3U30-25B | 2" *5.1 cm* | 5" *12.7 cm* | 3U | 5.25" *13.3 cm* |
| 3RR-4U30-25B | 2" *5.1 cm* | 5" *12.7 cm* | 4U | 7" *17.8 cm* |
| 3RR-5U30-25B | 2" *5.1 cm* | 5" *12.7 cm* | 5U | 8.75" *22.2 cm* |

## ACCESSORIES


**3SKB-SA**
**Shock Absorber Kit**
Set of 8 extra shock absorbers with a capable load range of 40 to 150 lbs (18 kg to 68 kg)
*Installed by factory only



**3SKB-SLP**
**Shipping Label Plate**
12" x 7" aluminum label (comes with installation kit)



**3SKB-SR30**
**30" Support Rails**
Zinc plated steel rails to support additional weight



# 24" REMOVABLE SHOCK RACKS

*When maximum shock absorption is needed with a sliding rack in the smallest exterior dimensions, this is the choice for this depth*

*Removable shock rack with patented "positive lock" latching system that slides open like a drawer*



MADE IN USA

YOU BREAK IT SKB LIFETIME WARRANTY 100% WE REPLACE IT

## FEATURES

- Completely removable frame for access to bench integration
- Meets or exceeds MIL-STD-810G/IP67
- Standard payload range 40 to 150 lbs
- Optional extended payload range 160 to 300 lbs (3SKB-SA*)
- Standard 19" rack width per ANSI/EIA-310-C
- Standard rack depth 24" rail to rail
- Square hole rack rails to accommodate either #10-32 US standard, or 6mm international standard cage nuts - hardware included
- 2" front lid, and 5" rear lid with edge casters (standard); other options available
- SKB's rugged roto-molded shell ensures industry leading strength and impact resistance
- Molded in stacking ribs and lugs are designed to stack with competitive manufacturers' cases
- Black powder coated stainless steel hardware (standard) which is recessed for protection
- 8 comfort grip spring loaded lift handles
- Automatic ambient pressure relief valve (standard)
- Lid hangers (standard)
- Case coupling straps (standard)

## AVAILABLE SIZES

| Model # | Lid Depth Front | Lid Depth Rear | Rack Units | Rack Height |
|---|---|---|---|---|
| 3RR-3U24-25B | 2" *5.1 cm* | 5" *12.7 cm* | 3U | 5.25" *13.3 cm* |
| 3RR-4U24-25B | 2" *5.1 cm* | 5" *12.7 cm* | 4U | 7" *17.8 cm* |
| 3RR-5U24-25B | 2" *5.1 cm* | 5" *12.7 cm* | 5U | 8.75" *22.2 cm* |
| 3RR-7U24-25B | 2" *5.1 cm* | 5" *12.7 cm* | 7U | 12.25" *31.1 cm* |
| 3RR-9U24-25B | 2" *5.1 cm* | 5" *12.7 cm* | 9U | 15.75" *40 cm* |
| 3RR-11U24-25B | 2" *5.1 cm* | 5" *12.7 cm* | 11U | 19.25" *48.9 cm* |
| 3RR-14U24-25B | 2" *5.1 cm* | 5" *12.7 cm* | 14U | 24.5" *62.2 cm* |

## ACCESSORIES


**3SKB-SA**
**Shock Absorber Kit**
Set of 8 extra shock absorbers with a capable load range of 40 to 150 lbs (18 kg to 68 kg)
*Installed by factory only



**3SKB-SLP**
**Shipping Label Plate**
12" x 7" aluminum label (comes with installation kit)



**3SKB-SR24**
**24" Support Rails**
Zinc plated steel rails to support additional weight




P.O. Box 936
Sykesville, MD 21784

SPECIALTY CASES

800-267-1674
www.specialtycases.com

# 20" REMOVABLE SHOCK RACKS

*When maximum shock absorption is needed with a sliding rack in the smallest exterior dimensions, this is the choice for this depth*



***Removable shock rack with patented "positive lock" latching system that slides open like a drawer***

## FEATURES

- Completely removable frame for access to bench integration
- Meets or exceeds MIL-STD-810G/IP67
- Standard payload range 40 to 150 lbs
- Optional extended payload range 160 to 300 lbs (3SKB-SA*)
- Standard 19" rack width per ANSI/EIA-310-C
- Standard rack depth 20" rail to rail
- Square hole rack rails to accommodate either #10-32 US standard, or 6mm international standard cage nuts - hardware included
- 2" front lid and 2" rear lid standard; other lid depths available
- SKB's rugged roto-molded shell ensures industry leading strength and impact resistance
- Molded in stacking ribs and lugs are designed to stack with competitive manufacturers' cases
- Black powder coated stainless steel hardware (standard) which is recessed for protection
- 8 comfort grip spring loaded lift handles
- Automatic ambient pressure relief valve (standard)
- Lid hangers (standard)
- Case coupling straps (standard)

## AVAILABLE SIZES

| Model # | Lid Depth Front | Lid Depth Rear | Rack Units | Rack Height |
|---|---|---|---|---|
| 3RR-3U20-22B | 2" *5.1 cm* | 2" *5.1 cm* | 3U | 5.25" *13.3 cm* |
| 3RR-4U20-22B | 2" *5.1 cm* | 2" *5.1 cm* | 4U | 7" *17.8 cm* |
| 3RR-5U20-22B | 2" *5.1 cm* | 2" *5.1 cm* | 5U | 8.75" *22.2 cm* |
| 3RR-6U20-22B | 2" *5.1 cm* | 2" *5.1 cm* | 6U | 10.5" *26.7 cm* |
| 3RR-7U20-22B | 2" *5.1 cm* | 2" *5.1 cm* | 7U | 12.25" *31.1 cm* |
| 3RR-9U20-22B | 2" *5.1 cm* | 2" *5.1 cm* | 9U | 15.75" *40 cm* |
| 3RR-11U20-22B | 2" *5.1 cm* | 2" *5.1 cm* | 11U | 19.25" *48.9 cm* |
| 3RR-14U20-22B | 2" *5.1 cm* | 2" *5.1 cm* | 14U | 24.5" *62.2 cm* |

## ACCESSORIES

**3SKB-SA**
**Shock Absorber Kit**
Set of 8 extra shock absorbers with a capable load range of 40 to 150 lbs (18 kg to 68 kg)
*Installed by factory only



**3SKB-SLP**
**Shipping Label Plate**
12" x 7" aluminum label (comes with installation kit)



**3SKB-SR20**
**20" Support Rails**
Zinc plated steel rails to support additional weight

