



SPECIALTY CASES

[DESIGN ■ SUPPORT ■ PROTECT]

Product Datasheet

Parker SW-T Series

SW2424-30T

Specifications

Lid Depth	15 in
Base Depth	15 in
Interior Length	24 in
Interior Width	24 in
Interior Height	30 in
Exterior Length	26 in
Exterior Width	25 in
Exterior Height	31 in
Carton Length	27 in
Carton Width	27 in
Carton Height	33 in

Max. Temperature	180° F
Min. Temperature	-180° F
Case Weight	41 lb
Exterior Color	White
# Inline Edge Wheels	4
Lockable	Yes
Removable Lid	Yes

Description

Parker Plastics' SW-T Series heavy duty ATA shipping containers feature in-line edge wheels and completely removable lids. Most of these cases are have a base/lid split close to the middle of the case. Constructed of high density polyethylene for unmatched strength and durability and available in an abundant variety of sizes. These cases have been used to ship everything you can imagine since the 1960's. Because they are built to last and are the safest way to transport your valuable equipment and products, they still are a favorite here.

Features

- In-line Edge Wheels and spring loaded tow handle.
- Removable Take Off Lids
- Different base/lid split than the traditional case.
- Water-resistant design
- ATA Spec 300
- Made in America
- Quarter turn military style latches
- Rubber gaskets to seal out dirt and moisture
- Valance is made with heavy duty, powder coated aluminum.
- Full length, heavy duty piano hinges
- Steel spring loaded heavy duty handles with rubber grip.
- Cases can be padlocked.
- Permanent white finish exterior withstands temperatures of -180 F° to 180 F° and is resistant to solvents.
- With so many sizes to choose from, you're sure to find just the right case for your product.
- Foam absorbs shock and will support weights of 250 lbs. per square inch.
- Available Interiors are Empty, 2 Inch Foam Lined around the entire inside perimeter of the case, and 2 Inch foam filled for a case that is completely filled with 2" layers of soft, shock-absorbing foam.

P.O. Box 936
Sykesville, MD 21784
www.SpecialtyCases.com

Last Updated
January 2017

Phone: 301-497-9032
Toll Free: 800-267-1674