



SPECIALTY CASES

[DESIGN ■ SUPPORT ■ PROTECT]

Product Datasheet

SKB 3SKB Series

1SKB-R910U20

Specifications

Lid Depth	3.25 in	8.26 cm
Interior Length	TBA	TBA
Interior Width	19.00 in	48.26 cm
Interior Height	17.50 in	44.45 cm
Interior Cu. Volume	3.85 cu ft	0.11 cu m
Space Units Total	10	10
Rackable Depth	20.00 in	50.80 cm
Depth Front Rail to Back Lid	24.50 in	62.23 cm
Exterior Depth	29.00 in	73.66 cm
Exterior Width	27.75 in	70.49 cm

Exterior Height	26.13 in	66.37 cm
Exterior Cu. Volume	12.17 cu ft	0.34 cu m
Carton Length	TBA	TBA
Carton Width	TBA	TBA
Carton Depth	TBA	TBA
Carton Cu. Volume	TBA	TBA
Product Weight	54.35 lb	24.65 kg
Shipping Weight	62.00 lb	28.12 kg
Color	Black	Black

Description

An internal frame mounted on adjustable elastomer shock absorbers on all eight corners. These revolutionary shocks are designed to control the effects of shock and vibration on three axes. The "sway" space around the internal frame provides natural air conditioning -- very important for delicate equipment. Inner rack chassis depth is 20" rail to rail with pre-threaded rack rails for standard 10-32 hardware that is included. They are half the weight of the old wooden cases.

Features

- Includes rear rails, front and rear doors
- Adjustable elastomer shock technology
- Precise level of shock absorption for any load
- Molded handles provide an easy and secure grasping point
- Mounting hardware in the racks is easy with the provided hardware