



# SPECIALTY CASES

[DESIGN ■ SUPPORT ■ PROTECT]

Product Datasheet

## Parker SC-T Series

## SC2424-24T

### Specifications

|                 |       |
|-----------------|-------|
| Lid Depth       | 12 in |
| Base Depth      | 12 in |
| Interior Length | 24 in |
| Interior Width  | 24 in |
| Interior Height | 24 in |
| Exterior Length | 26 in |
| Exterior Width  | 25 in |
| Exterior Height | 25 in |
| Carton Length   | 27 in |
| Carton Width    | 26 in |
| Carton Height   | 27 in |

|                  |         |
|------------------|---------|
| Max. Temperature | 180° F  |
| Min. Temperature | -180° F |
| Case Weight      | 31 lb   |
| Exterior Color   | White   |
| Wheels           | No      |
| Lockable         | Yes     |
| Removable Lid    | Yes     |

### Description

Parker Plastics' SC-T Series heavy duty ATA shipping containers feature completely removable lids. Most of these cases are have a base/lid split close to the middle of the case. Constructed of high density polyethylene for unmatched strength and durability and available in an abundant variety of sizes. These cases have been used to ship everything you can imagine since the 1960's. Because they are built to last and are the safest way to transport your valuable equipment and products, they still are a favorite here.

### Features

- ATA Spec 300
- Take off lid with base/lid split close to the middle of case.
- Water-resistant design
- Quarter turn military style latches
- Rubber gaskets to seal out dirt and moisture
- Valance is made with heavy duty, powder coated aluminum.
- Full length, heavy duty piano hinges
- Steel spring loaded heavy duty handles with rubber grip.
- Cases can be padlocked.
- Permanent white finish exterior withstands temperatures of -180 F° to 180 F° and is resistant to solvents.
- Many sizes to choose from helps you to find just the right case for your equipment.
- Proudly made in America
- Foam absorbs shock and will support weights of 250 lbs. per square inch.
- Available Interiors are Empty, 2 Inch Foam Lined around the entire inside perimeter of the case, and 2 Inch foam filled for a case that is completely filled with 2" layers of soft, shock-absorbing foam.