

Specifications

Interior dimensions	15.0" x 10.5" x 6.2" 381 mm x 267 mm x 157 mm
Exterior dimensions	16.7" x 13.4" x 6.8" 424 mm x 340 mm x 173 mm
Weight (empty)	5.1 lb 2.3 kg
Volume	16 L
Temperature Range	Mini -67°F (-55°C) Max 158°F (70°C)
Max Buoyancy	40.7 lb 18.5 kg



Available Colors



In addition to the fact that NANUK-R cases are designed for long-term use and recyclability, the shell of the NANUK-R Collection is made from a minimum of 95% post-consumer recycled resin.



UPC Code	Item Number	Description
666365110794	920SR000BK-0A0	Nanuk-R 920 Collection - Black
666365112811	920SR010BK-0A0	Nanuk-R 920 Collection w/foam - Black

CERTIFICATIONS



**DEF-STAN 81-41
STANAG 4280**
*Dry Heat / Low temp
Vibration / Water spray-rain
Impact-Drop*



MIL-STD-810H
*High temp / Low temp
Water Spray-Rain / Immersion
Vibration / Transit Drop*



IP67
*Dustproof
Immersion*



**Specifications
ATA 300**
*Category 1
Impact Test*



**LIFETIME
WARRANTY**



**MILITARY
APPROVED**



**CRUSHPROOF
RESIN**



**RECYCLED
RESIN**

