



SPECIALTY CASES

[DESIGN ■ SUPPORT ■ PROTECT]

Product Datasheet

SKB iSeries

3i-1208-3

Specifications

| | | | | | |
|---------------------|------------|-----------|-------------------|------------|-----------|
| Lid Depth | 0.50 in | 1.27 cm | Max. Temperature | 180.00° F | 82.22° C |
| Base Depth | 2.75 in | 6.99 cm | Min. Temperature | -69.00° F | -56.11° C |
| Interior Length | 12.00 in | 30.48 cm | Max. Buoyancy | 10.00 lb | 6.00 kg |
| Interior Width | 8.00 in | 20.32 cm | Carton Length | 13.50 in | 34.29 cm |
| Interior Depth | 3.25 in | 8.26 cm | Carton Width | 10.50 in | 26.67 cm |
| Interior Cu. Volume | 0.18 cu ft | 0.01 cu m | Carton Depth | 4.00 in | 10.16 cm |
| Exterior Length | 12.86 in | 32.66 cm | Carton Cu. Volume | 0.33 cu ft | 0.01 cu m |
| Exterior Width | 9.70 in | 24.64 cm | Product Weight | 2.12 lb | 0.96 kg |
| Exterior Depth | 3.80 in | 9.65 cm | Shipping Weight | 2.58 lb | 1.17 kg |
| Exterior Cu. Volume | 0.27 cu ft | 0.01 cu m | Color | Black | Black |

Description

SKB iSeries injection molded waterproof cases are constructed of ultra high-strength polypropylene copolymer resin. Each case is waterproof and dust tight with a submersible design (IP67) that is resistant to corrosion and impact damage. Its molded-in hinge, patented "trigger release" latch system, comfortable, snap-down rubber over-molded cushion grip handle, secure stacking, and automatic ambient pressure equalization valve (MIL-STD 648C) all contribute to its military grade design. Resistant to UV, solvents, corrosion, and fungus per MIL-STD-810F.

Features

- Injection molded - High impact strength, 2.8x stronger than our competition
- Lightweight - Lighter than the competition
- Interior options available
- Field replaceable hardware - Latches, handles, hinges and wheels
- Best latches in the industry - Trigger latches, open quickly and easily with one finger operation
- TSA lock options - Easy transportation through airport security
- 44 sizes and counting

P.O. Box 936
 Sykesville, MD 21784
www.SpecialtyCases.com

Phone: 301-497-9032
 Toll Free: 800-267-1674