

[DESIGN = SUPPORT = PROTECT]

SKB iSeries

Product Datasheet

3i-1309-6

Specifications

Lid Depth	1.50 in	3.81 cm
Base Depth	5.00 in	12.70 cm
Interior Length	13.50 in	34.29 cm
Interior Width	9.50 in	24.13 cm
Interior Depth	6.50 in	16.51 cm
Interior Cu. Volume	0.48 cu ft	0.01 cu m
Exterior Length	14.73 in	37.41 cm
Exterior Width	11.94 in	30.33 cm
Exterior Depth	7.31 in	18.57 cm
Exterior Cu. Volume	0.74 cu ft	0.02 cu m

Max. Temperature	180.00° F	82.22° C
Min. Temperature	-69.00° F	-56.11° C
Max. Buoyancy	31.00 lb	14.00 kg
Carton Length	15.50 in	39.37 cm
Carton Width	12.25 in	31.12 cm
Carton Depth	7.75 in	19.69 cm
Carton Cu. Volume	0.84 cu ft	0.02 cu m
Product Weight	4.60 lb	2.08 kg
Shipping Weight	5.55 lb	2.52 kg

Description

SKB iSeries injection molded waterproof cases are constructed of ultra high-strength polypropylene copolymer resin. Each case is waterproof and dust tight with a submersible design (IP67) that is resistant to corrosion and impact damage. Its molded-in hinge, patented "trigger release" latch system, comfortable, snapdown rubber over-molded cushion grip handle, secure stacking, and automatic ambient pressure equalization valve (MIL-STD 648C) all contribute to its military grade design. Resistant to UV, solvents, corrosion, and fungus per MIL-STD-810F.

Features

- Injection molded High impact strength, 2.8x stronger than our competition
- Lightweight Lighter than the competition
- Interior options available
- Field replaceable hardware Latches, handles, hinges and wheels
- Best latches in the industry Trigger latches, open quickly and easily with one finger operation
- TSA lock options Easy transportation through airport security
- 44 sizes and counting

P.O. Box 936 Sykesville, MD 21784 www.SpecialtyCases.com

Last Updated July 2020 Phone: 301-497-9032 Toll Free: 800-267-1674