



SPECIALTY CASES

[DESIGN ■ SUPPORT ■ PROTECT]

Product Datasheet

SKB iSeries

3i-1610-5

Specifications

| | | |
|---------------------|------------|-----------|
| Lid Depth | 2.00 in | 5.08 cm |
| Base Depth | 3.50 in | 8.89 cm |
| Interior Length | 16.00 in | 40.64 cm |
| Interior Width | 10.00 in | 25.40 cm |
| Interior Depth | 5.50 in | 13.97 cm |
| Interior Cu. Volume | 0.51 cu ft | 0.01 cu m |
| Exterior Length | 17.17 in | 43.61 cm |
| Exterior Width | 12.17 in | 30.91 cm |
| Exterior Depth | 6.21 in | 15.77 cm |
| Exterior Cu. Volume | 0.75 cu ft | 0.02 cu m |

| | | |
|-------------------|------------|-----------|
| Max. Temperature | 180.00° F | 82.22° C |
| Min. Temperature | -69.00° F | -56.11° C |
| Max. Buoyancy | 32.00 lb | 15.00 kg |
| Carton Length | 17.50 in | 44.45 cm |
| Carton Width | 13.00 in | 33.02 cm |
| Carton Depth | 6.50 in | 16.51 cm |
| Carton Cu. Volume | 0.86 cu ft | 0.02 cu m |
| Product Weight | 5.00 lb | 2.26 kg |
| Shipping Weight | 5.95 lb | 2.70 kg |

Description

SKB iSeries injection molded waterproof cases are constructed of ultra high-strength polypropylene copolymer resin. Each case is waterproof and dust tight with a submersible design (IP67) that is resistant to corrosion and impact damage. Its molded-in hinge, patented "trigger release" latch system, comfortable, snap-down rubber over-molded cushion grip handle, secure stacking, and automatic ambient pressure equalization valve (MIL-STD 648C) all contribute to its military grade design. Resistant to UV, solvents, corrosion, and fungus per MIL-STD-810F.

Features

- Injection molded - High impact strength, 2.8x stronger than our competition
- Lightweight - Lighter than the competition
- Interior options available
- Field replaceable hardware - Latches, handles, hinges and wheels
- Best latches in the industry - Trigger latches, open quickly and easily with one finger operation
- TSA lock options - Easy transportation through airport security
- 44 sizes and counting