



# SPECIALTY CASES

[DESIGN ■ SUPPORT ■ PROTECT]

Product Datasheet

SKB iSeries

3i-1914N-8B-E

## Specifications

Lid Depth	2.00 in	5.08 cm
Base Depth	6.00 in	15.24 cm
Interior Length	19.00 in	48.26 cm
Interior Width	14.50 in	36.83 cm
Interior Depth	8.00 in	20.32 cm
Interior Cu. Volume	1.28 cu ft	0.04 cu m
Exterior Length	20.25 in	51.44 cm
Exterior Width	16.93 in	43.00 cm
Exterior Depth	8.78 in	22.30 cm
Exterior Cu. Volume	1.74 cu ft	0.05 cu m

Max. Temperature	180.00° F	82.22° C
Min. Temperature	-69.00° F	-56.11° C
Max. Buoyancy	80.00 lb	37.00 kg
Carton Length	21.00 in	53.34 cm
Carton Width	17.50 in	44.45 cm
Carton Depth	9.50 in	24.13 cm
Carton Cu. Volume	2.02 cu ft	0.06 cu m
Product Weight	8.00 lb	3.63 kg
Shipping Weight	9.65 lb	4.38 kg
Color	Black	Black

## Description

SKB iSeries injection molded waterproof cases are constructed of ultra high-strength polypropylene copolymer resin. Each case is waterproof and dust tight with a submersible design (IP67) that is resistant to corrosion and impact damage. Its molded-in hinge, patented "trigger release" latch system, comfortable, snap-down rubber over-molded cushion grip handle, secure stacking, and automatic ambient pressure equalization valve (MIL-STD 648C) all contribute to its military grade design. Resistant to UV, solvents, corrosion, and fungus per MIL-STD-810F.

## Features

- Injection molded - High impact strength, 2.8x stronger than our competition
- Lightweight - Lighter than the competition
- Interior options - Empty, cubed, layered foam, padded dividers or custom foam
- Field replaceable hardware - Latches, handles, hinges and wheels
- Best latches in the industry - Trigger latches, open quickly and easily with one finger operation
- TSA lock options - Easy transportation through airport security
- 44 sizes and counting