



SPECIALTY CASES

[DESIGN ■ SUPPORT ■ PROTECT]

Product Datasheet

SKB iSeries

3i-2222-12

Specifications

Lid Depth	2.00 in	5.08 cm	Max. Temperature	180.00° F	82.22° C
Base Depth	10.50 in	26.67 cm	Min. Temperature	-69.00° F	-56.11° C
Interior Length	22.50 in	57.15 cm	Max. Buoyancy	229.00 lb	104.00 kg
Interior Width	22.50 in	57.15 cm	Carton Length	25.50 in	64.77 cm
Interior Depth	12.50 in	31.75 cm	Carton Width	25.50 in	64.77 cm
Interior Cu. Volume	3.66 cu ft	0.10 cu m	Carton Depth	14.75 in	37.47 cm
Exterior Length	24.81 in	63.02 cm	Carton Cu. Volume	5.55 cu ft	0.16 cu m
Exterior Width	24.98 in	63.45 cm	Product Weight	20.60 lb	9.34 kg
Exterior Depth	14.15 in	35.94 cm	Shipping Weight	24.00 lb	10.89 kg
Exterior Cu. Volume	5.07 cu ft	0.14 cu m	Color	Black	Black

Description

SKB iSeries injection molded waterproof cases are constructed of ultra high-strength polypropylene copolymer resin. Each case is waterproof and dust tight with a submersible design (IP67) that is resistant to corrosion and impact damage. Its molded-in hinge, patented "trigger release" latch system, comfortable, snap-down rubber over-molded cushion grip handle, secure stacking, and automatic ambient pressure equalization valve (MIL-STD 648C) all contribute to its military grade design. Resistant to UV, solvents, corrosion, and fungus per MIL-STD-810F.

Features

- Injection molded - High impact strength, 2.8x stronger than our competition
- Lightweight - Lighter than the competition
- Interior options available
- Field replaceable hardware - Latches, handles, hinges and wheels
- Best latches in the industry - Trigger latches, open quickly and easily with one finger operation
- TSA lock options - Easy transportation through airport security
- 44 sizes and counting