



SPECIALTY CASES

[DESIGN ■ SUPPORT ■ PROTECT]

Product Datasheet

SKB iSeries

3i-4213-12

Specifications

| | | | | | |
|---------------------|------------|-----------|-------------------|------------|-----------|
| Lid Depth | 2.00 in | 5.08 cm | Max. Temperature | 180.00° F | 82.22° C |
| Base Depth | 10.00 in | 25.40 cm | Min. Temperature | -69.00° F | -56.11° C |
| Interior Length | 42.50 in | 107.95 cm | Max. Buoyancy | 249.00 lb | 113.00 kg |
| Interior Width | 13.50 in | 34.29 cm | Carton Length | 46.00 in | 116.84 cm |
| Interior Depth | 12.00 in | 30.48 cm | Carton Width | 16.38 in | 41.61 cm |
| Interior Cu. Volume | 3.98 cu ft | 0.11 cu m | Carton Depth | 13.50 in | 34.29 cm |
| Exterior Length | 45.10 in | 114.55 cm | Carton Cu. Volume | 5.89 cu ft | 0.17 cu m |
| Exterior Width | 16.03 in | 40.72 cm | Product Weight | 22.60 lb | 10.25 kg |
| Exterior Depth | 12.97 in | 32.94 cm | Shipping Weight | 25.75 lb | 11.68 kg |
| Exterior Cu. Volume | 5.43 cu ft | 0.15 cu m | Color | Black | Black |

Description

SKB iSeries injection molded waterproof cases are constructed of ultra high-strength polypropylene copolymer resin. Each case is waterproof and dust tight with a submersible design (IP67) that is resistant to corrosion and impact damage. Its molded-in hinge, patented "trigger release" latch system, comfortable, snap-down rubber over-molded cushion grip handle, secure stacking, and automatic ambient pressure equalization valve (MIL-STD 648C) all contribute to its military grade design. Resistant to UV, solvents, corrosion, and fungus per MIL-STD-810F.

Features

- Injection molded - High impact strength, 2.8x stronger than our competition
- Lightweight - Lighter than the competition
- Interior options available
- Field replaceable hardware - Latches, handles, hinges and wheels
- Best latches in the industry - Trigger latches, open quickly and easily with one finger operation
- TSA lock options - Easy transportation through airport security
- 44 sizes and counting