



SPECIALTY CASES

[DESIGN ■ SUPPORT ■ PROTECT]

Product Datasheet

SKB 3RR Removable Rack Series

3RR-3U30-25B

Specifications

Interior Length	30.00 in	76.20 cm
Interior Width	19.00 in	48.26 cm
Interior Height	5.25 in	13.34 cm
Interior Cu. Volume	1.73 cu ft	0.05 cu m
Space Units Total	3	3
Rackable Depth	30.00 in	76.20 cm
Depth Front Rail to Back Lid	TBA	TBA
Exterior Depth	45.03 in	114.38 cm
Exterior Width	23.80 in	60.45 cm

Exterior Height	11.82 in	30.02 cm
Exterior Cu. Volume	7.33 cu ft	0.21 cu m
Carton Length	45.25 in	114.94 cm
Carton Width	24.50 in	62.23 cm
Carton Depth	12.50 in	31.75 cm
Carton Cu. Volume	8.02 cu ft	0.23 cu m
Product Weight	63.20 lb	28.67 kg
Shipping Weight	68.00 lb	30.84 kg
Color	Black	Black

Description

SKB's 3RR Series Removable Shock Rack are lightweight, shockproof, watertight, dustproof, heat and chemical resistant, perfect for protecting and transporting your sensitive electronic equipment. Molded of LMDP Linear Medium Density Polyethylene plastic that meets or exceed MIL-STD 810G standards and includes 8 elastomeric shock absorbers which allows a standard payload range of 40 to 150 pounds. The rugged roto-molded shell ensures industry leading strength and impact resistance. The standard COTS (commercial off the shelf) case comes with a 2" deep front lid and a 5" deep rear lid to accommodate longer rack gear, and edge casters to allow convenient case transport.

Molded-in stacking ribs and lugs are designed to stack with competitive manufacturers cases. Black powder coated stainless steel hardware are recessed for protection is standard as well as 8 comfort grip spring loaded lift handles which allow for easy movement. An automatic pressure relief valve is another standard feature along with gasket sealed lids that include convenient lid hangers to store your lids when your equipment is in operation. Coupling straps are included for securing the racks together when stacked. The interior of the case features a removable rack with a patent pending "positive lock" latching system that slides open like a file drawer, allowing full access to racked equipment. The interior rack is also completely removable allowing complete frame access for bench integration.

Features

- Completely removable frame for access to bench integration
- Meets or Exceeds MIL-STD 810G
- Standard payload range 40 to 150 lbs
- Optional extended payload range 160 to 300 lbs
- Standard 19" Rack width per ANSI/EIA-310-C
- Square hold rack rails to accommodate either #10-32 US standard, or 6mm international standard cage nuts
- 2" front lid, and 5" rear lid with edge casters standard, other options available
- SKB's Rugged roto-molded shell ensures industry leading strength and impact resistance
- Molded in stacking ribs and lugs are designed to stack with competitive manufacturers cases
- Black powder coated stainless steel hardware (standard) which are recessed for protection
- 8 comfort grip spring loaded lift handles
- Automatic pressure relief valve (standard)
- Lid hangars (standard)
- Case coupling straps (standard)

P.O. Box 936
 Sykesville, MD 21784
www.SpecialtyCases.com

Phone: 301-497-9032
 Toll Free: 800-267-1674

Last Updated
 January 2023