



SPECIALTY CASES

[DESIGN ■ SUPPORT ■ PROTECT]

Product Datasheet

SKB 3RR Removable Rack Series

3RR-5U20-22B

Specifications

Lid Depth	2 in	5.08 cm
Base Depth	2 in	5.08 cm
Interior Length	24 in	60.96 cm
Interior Width	19 in	48.26 cm
Interior Depth	8.75 in	22.23 cm
Interior Cu. Volume	1.92 cu ft	0.05 cu m
Exterior Length	32.3 in	82.04 cm
Exterior Width	23.9 in	60.71 cm
Exterior Depth	15.3 in	38.86 cm

Rack Space Units	5	5
Max. Temperature	180° F	82.22° C
Min. Temperature	-40° F	-40° C
Carton Length	33 in	83.82 cm
Carton Width	24.5 in	62.23 cm
Carton Depth	16.13 in	40.97 cm
Weight	50.2 lbs	22.77 kg
Color	Black	Black

Description

SKB's 3RR Series Removable Shock Rack are lightweight, shockproof, watertight, dustproof, heat and chemical resistant, perfect for protecting and transporting your sensitive electronic equipment. Molded of LMDP Linear Medium Density Polyethylene plastic that meets or exceeds MIL-STD 810G standards, these Shock Racks also include 8 elastomeric shock absorbers which allow for a standard payload range of 40 to 150 lbs (optional extended payload range of 160 to 300 lbs can be accommodated as a special order option). The 20 in. 3RR Series Removable Racks are 20 inches deep from rail to rail with a standard 19 in. rack width per ANSI/EIA-310-C specification and feature square-hole rack rails to accommodate either #10-32 US standard or 6mm International standard cage nuts which are supplied with the cases.

Features

- Completely removable frame for access to bench integration
- Meets or exceeds MIL-STD 810G
- Standard payload range of 40 to 150 lbs
- Optional extended payload range 160 to 300 lbs
- Standard 19 in. rack width per ANSI/EIA-310-C
- Standard rack depth 20 in. rail to rail
- Square hole rack rails to accommodate either #10-32 US standard or 6mm international standard cage nuts
- 2 in. front and rear lids
- Rugged roto-molded shell ensures industry leading strength and impact resistance
- Molded in stacking ribs and lugs are designed to stack with all SKB 3RR & 3RS cases, as well as competitive manufacturer cases
- Recessed black powder coated stainless steel hardware
- Four (4) comfort grip spring loaded lift handles
- Automatic pressure relief valve (standard)
- Lid hangers (standard)
- Case coupling straps (standard)
- IP67 Certified for protection of dust ingress and water submersion (1 meter submersion for 30 minutes)
- Includes Million Mile Warranty
- Proudly Made in the USA

P.O. Box 936
 Sykesville, MD 21784
www.SpecialtyCases.com

Phone: 301-497-9032
 Toll Free: 800-267-1674