



SPECIALTY CASES

[DESIGN ■ SUPPORT ■ PROTECT]

Product Datasheet

SKB 3RS Static Shock Rack Series

3RS-3U24-25B

Specifications

Interior Length	31.00 in	78.74 cm	Exterior Height	11.94 in	30.33 cm
Interior Width	19.00 in	48.26 cm	Exterior Cu. Volume	6.42 cu ft	0.18 cu m
Interior Height	5.50 in	13.97 cm	Carton Length	40.25 in	102.24 cm
Interior Cu. Volume	1.45 cu ft	0.04 cu m	Carton Width	24.50 in	62.23 cm
Space Units Total	3	3	Carton Depth	12.25 in	31.12 cm
Rackable Depth	24.00 in	60.96 cm	Carton Cu. Volume	6.99 cu ft	0.20 cu m
Depth Front Rail to Back Lid	29.00 in	73.66 cm	Product Weight	46.60 lb	21.14 kg
Exterior Depth	39.05 in	99.19 cm	Shipping Weight	51.00 lb	23.13 kg
Exterior Width	23.80 in	60.45 cm	Color	Black	Black

Description

SKB's 3RS Series Static Shock Rack Transport cases are lightweight, shockproof, watertight, dustproof, heat and chemical resistant, perfect for protecting and transporting your sensitive electronic equipment. The 3RS Series Static Shock Racks are available in 24" or 30" deep from rail to rail with a standard 19" rack width and feature square-hole rack rails to accommodate either #10-32 US standard, or 6mm International standard cage nuts which are supplied with the cases.

The rugged roto-molded shell ensures industry leading strength and impact resistance. Molded-in stacking ribs and lugs are designed to stack with competitive manufacturers cases. Coupling straps are included for securing the racks together when stacked.

Features

- Meets or Exceeds MIL-STD 810G
- Standard payload range 40 to 150 lbs
- Optional extended payload range 160 to 300 lbs
- Standard 19" Rack width per ANSI/EIA-310-C
- Square hold rack rails to accommodate either #10-32 US standard, or 6mm international standard cage nuts
- 2" front lid, and 5" rear lid with edge casters standard, other options available
- SKB's Rugged roto-molded shell ensures industry leading strength and impact resistance
- Molded in stacking ribs and lugs are designed to stack with competitive manufacturers cases
- Black powder coated stainless steel hardware (standard) which are recessed for protection
- 8 comfort grip spring loaded lift handles
- Automatic pressure relief valve (standard)
- Lid hangars (standard)
- Case coupling straps (standard)
- Reduced Footprint
- Low Profile
- Light Weight
- Lifetime Warranty

P.O. Box 936
Sykesville, MD 21784
www.SpecialtyCases.com

Phone: 301-497-9032
Toll Free: 800-267-1674