



# SPECIALTY CASES

[DESIGN ■ SUPPORT ■ PROTECT]

Product Datasheet

## SKB 3RS Static Shock Rack Series

## 3RS-7U24-25B

### Specifications

|                              |            |           |
|------------------------------|------------|-----------|
| Interior Length              | 31.00 in   | 78.74 cm  |
| Interior Width               | 19.00 in   | 48.26 cm  |
| Interior Height              | 12.25 in   | 31.12 cm  |
| Interior Cu. Volume          | 3.23 cu ft | 0.09 cu m |
| Space Units Total            | 7          | 7         |
| Rackable Depth               | 24.00 in   | 60.96 cm  |
| Depth Front Rail to Back Lid | 29.00 in   | 73.66 cm  |
| Exterior Depth               | 39.05 in   | 99.19 cm  |
| Exterior Width               | 23.80 in   | 60.45 cm  |

|                     |             |           |
|---------------------|-------------|-----------|
| Exterior Height     | 18.84 in    | 47.85 cm  |
| Exterior Cu. Volume | 10.13 cu ft | 0.29 cu m |
| Carton Length       | 40.25 in    | 102.24 cm |
| Carton Width        | 24.50 in    | 62.23 cm  |
| Carton Depth        | 19.25 in    | 48.90 cm  |
| Carton Cu. Volume   | 10.99 cu ft | 0.31 cu m |
| Product Weight      | TBA         | TBA       |
| Shipping Weight     | TBA         | TBA       |
| Color               | Black       | Black     |

### Description

SKB's 3RS Series Static Shock Rack Transport cases are lightweight, shockproof, watertight, dustproof, heat and chemical resistant, perfect for protecting and transporting your sensitive electronic equipment. The 3RS Series Static Shock Racks are available in 24" or 30" deep from rail to rail with a standard 19" rack width and feature square-hole rack rails to accommodate either #10-32 US standard, or 6mm International standard cage nuts which are supplied with the cases.

The rugged roto-molded shell ensures industry leading strength and impact resistance. Molded-in stacking ribs and lugs are designed to stack with competitive manufacturers cases. Coupling straps are included for securing the racks together when stacked.

### Features

- Meets or Exceeds MIL-STD 810G
- Standard payload range 40 to 150 lbs
- Optional extended payload range 160 to 300 lbs
- Standard 19" Rack width per ANSI/EIA-310-C
- Square hold rack rails to accommodate either #10-32 US standard, or 6mm international standard cage nuts
- 2" front lid, and 5" rear lid with edge casters standard, other options available
- SKB's Rugged roto-molded shell ensures industry leading strength and impact resistance
- Molded in stacking ribs and lugs are designed to stack with competitive manufacturers cases
- Black powder coated stainless steel hardware (standard) which are recessed for protection
- 8 comfort grip spring loaded lift handles
- Automatic pressure relief valve (standard)
- Lid hangars (standard)
- Case coupling straps (standard)
- Reduced Footprint
- Low Profile
- Light Weight
- Lifetime Warranty

P.O. Box 936  
Sykesville, MD 21784  
[www.SpecialtyCases.com](http://www.SpecialtyCases.com)

Phone: 301-497-9032  
Toll Free: 800-267-1674

Last Updated  
January 2023