



SPECIALTY CASES

[DESIGN ■ SUPPORT ■ PROTECT]

Product Datasheet

SKB 3SKB Series

3SKB-R906U28

Specifications

Lid Depth	4.50 in	11.43 cm
Interior Length	TBA	TBA
Interior Width	19.00 in	48.26 cm
Interior Height	10.50 in	26.67 cm
Interior Cu. Volume	3.38 cu ft	0.10 cu m
Space Units Total	6	6
Rackable Depth	29.25 in	74.30 cm
Depth Front Rail to Back Lid	33.75 in	85.73 cm
Exterior Depth	TBA	TBA
Exterior Width	TBA	TBA

Exterior Height	TBA	TBA
Exterior Cu. Volume	12.68 cu ft	0.36 cu m
Carton Length	43.00 in	109.22 cm
Carton Width	26.50 in	67.31 cm
Carton Depth	20.50 in	52.07 cm
Carton Cu. Volume	13.52 cu ft	0.38 cu m
Product Weight	67.80 lb	30.75 kg
Shipping Weight	76.00 lb	34.47 kg
Color	Black	Black

Description

28 inch Heavy Duty Shockrack systems include a revolutionary new patented Adjustable Rail Conversion System. This ARCS technology allows the user to adjust the rack width up to 0.5 inches on each side and optional easy-mount adapter rails will convert the equipment mounting standard from 3/16" threaded to 7/32" through holes or square cage nut windows. The 7/32" through hole option and the 3/16" threaded are special order items. Accommodates Dell and Compaq servers utilizing "Versa-rail" or "Rapid-rail" pull-out systems.

Standard features include: (patent pending) compound hinged doors, black powder coated stainless steel latches, removable 4" casters. The inner rack chassis is built of high strength / lightweight aluminum alloy and 11-gauge hot rolled carbon steel rack rails to DIA-310 standards. Shock and vibration mitigation is accomplished with eight (8) elastomeric isolators rated for a payload range of 40 lbs. to 150 lbs. in a standard configuration and up to 300 pounds in a special order extended payload configuration allowing adequate sway space for ambient air circulation and heat dissipation with black powder coated stainless steel latches, gasketed doors and pressure relief valve.

Features

- Includes Adjustable Rail Conversion System (ARCS)
- Patent pending compound hinged doors
- Rear rails
- Casters
- Shock and water resistant
- Gasketed doors
- Pressure relief valve
- Stainless steel key-lockable field replaceable latches
- Removable 4" casters standard
- Stacks securely with the wheels on or off
- Recessed latches
- Adjustable elastomer shock absorbers
- Provisions to add additional shocks
- Roto molded for strength

P.O. Box 936
 Sykesville, MD 21784
www.SpecialtyCases.com

Phone: 301-497-9032
 Toll Free: 800-267-1674